









On Grid Energy Storage System (ESS)
COMPLETE SOLUTION for Residential Applications

SMILE 5

with 13.3P battery


Key Features

-  **Elegant Design**
Unified design of the whole unit
-  **Outdoor**
IP65 rating can be installed outdoor
-  **UPS**
Uninterrupted power supply in 0.01S
-  **VPP Ready**
Compatible with Discover Energy VPP function
-  **High Energy Density**
44.6Wh per Litres
-  **Quick Installation**
Plug and play design, significantly reduce installation time



Real-time Monitoring

All systems can be monitored by **Web and iOS/Android APP**.



Safest Chemistry

AlphaESS uses Li-phosphate for its excellent safety and long lifespan.



Battery Specifications	
Model	SMILE-BAT-13.3P
Battery Type	LFP (LiFePO4)
System Weight	120 kg
Dimension (W x D x H)	610 x 236 x 812 mm
IP Protection	IP65
Warranty	5 Year Product Warranty, 10 Year Performance Warranty, ≥ 8000 Cycle Life
Electrical	
Energy Capacity	13.34 kWh
Usable Capacity	13.34 kWh
Depth of Discharge (DoD)	100%
Nominal Voltage	48 V
Operating Voltage Range	45 ~ 54 V
Internal Resistance	≤ 20 mΩ
Operation	
Max. Charging Current	100 A (0.35C)
Max. Discharging Current	100 A (0.35C)
Operating Temperature Range	-10 °C ~ 50 °C*
Humidity	15% ~ 85%
BMS	
Modules Connection	1~6 in parallel (with expansion pack)
Power Consumption	<1 W (Work), <10 mW (Sleep)
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature measurement
Communication	CAN and RS-485 compatible
Certificate	
Transportation	UN38.3
Safety	IEC 62619 (Cell), IEC 62619 (Pack)

*When the temperature is below 0 °C or above 40 °C, the performance will be limited.

Inverter	SMILE5 INV
PV String Input Data	
Max. DC Input Power [W]	6660
The maximum DC input power for STC [W] (Small-scale Technology Certificates)	6600
Max. DC Voltage [V]	580
MPPT Voltage Range [V]	125~550
Starting Voltage [V]	125
Max. DC Current [A]	12/12
No. of DC Connectors	2
No. of MPPTs	2
DC Connector	MC4
Battery Input Data	
Nominal Voltage [V]	51.2
Max. Charging Voltage [V]	57.6
Max. Charging Current [A]	100
Max. Discharging Current [A]	100
AC Output Data (On Grid)	
Nominal AC Power [VA]	5000
Max. AC Power [VA]	5000
Max. AC Current [A]	21.7
Nominal Output Voltage [V]	230
Nominal Output Frequency [Hz]	50/60
THDi	<3%
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)
AC Output Data (Buck-Up)	
Nominal AC Power [VA]	4600
Peak AC Power [VA]	5200, 2 sec
Nominal Output Voltage [V]	230
Nominal Output Frequency [Hz]	50/60
Efficiency	
Max. Efficiency	97.60%
Europe Efficiency	97.00%
MPPT Adaptation Efficiency	99.90%
Protection	
Residual Current Monitoring Unit	Integrated
Anti-islanding Protection	Integrated
AC Over Current Protection	Integrated
Insulation Monitoring	Integrated
General Data	
Dimensions (WxHxD) [mm]	1604 x 610 x 236.6
Weight [kg]	17
Ambient Temperature Range [°C]	-10~50
Relative Humidity	0-95%
Protection Degree	IP65
Topology	High Frequency Isolation
Standby Losses [W]	<13
Cooling	Nature Convection
Noise Emission [dB]	<25
Monitoring	RS485; CAN; Wi-Fi
Standard Warranty [Years]	5
Certificates & Standards	
Grid Regulation	VDE-AR-N 4105, VDE 0126-1-1, AS 4777.2/3, CEI 0-21, G59/3, RD 1699, NRS 097-2-1
EMC	EN 61000-6-1/2/3/4
Safety Regulation	IEC 62109-1&-2, IEC 62477-1, IEC 62040.1.1, IEC 62116